

Universe	Professional
Type	Verticality
Category	Descenders
Subcategory	Self-braking descenders



RIG®


RIG is a compact self-braking descender for rope access, designed for experienced users. It has an ergonomic handle that allows comfortable descent control. The AUTO-LOCK system allows users to easily position themselves at a workstation without having to manipulate the handle or tie off the device. Once locked, the rope can be taken up without having to manipulate the handle. The safety gate allows the rope to be installed while the device remains connected to the harness.



The descender has a safety gate on the moving side plate that allows the user to easily install the rope while the device remains connected to the harness.



The ergonomic handle allows the user to unblock the rope and comfortably control the descent.



The AUTO-LOCK system allows users to easily position themselves at a workstation without having to manipulate the handle or tie off the device: as soon as the user releases the handle, the rope is automatically locked in the device.



The cam can be manipulated to feed out slack easily or belay a lead using climbing techniques.

Short Description Compact self-braking descender for rope access, designed for experienced users

Selling Points

- Designed for experienced rope access workers
- Easy to use:
 - Safety gate on the moving side plate allows the rope to be easily installed while the device remains connected to the harness, making it easier to pass intermediate anchors
 - Markings and rope guide makes it easy to install the rope
 - Ergonomic handle allows the rope to be released and enables comfortable control of the descent; there are two possible descent modes: on the side plate or in the V-shaped friction channel
 - AUTO-LOCK system allows users to easily position themselves at a workstation without having to manipulate the handle or tie off the device: as soon as the user releases the handle, the rope is automatically locked in the device; the automatic return system on the handle limits the risk of the device getting accidentally snagged
 - Handle automatically switches to storage position when the rope is removed from the device, reducing the risk of accidental snagging when the descender is carried on the harness
- Versatile:
 - Once locked, the rope can be taken up without having to manipulate the handle, allowing for easy short ascents, for example
 - Cam can be manipulated to feed out slack easily or belay a lead climber using climbing techniques
- The stainless steel wear plate improves durability by reinforcing the rope friction zone
- Lowering load: Up to 150 kg for one person, and up to 200 kg when used for rescue
- Rope compatibility: 10 to 11.5 mm diameter
- Available in two colors: yellow and black

Specification

- Material(s): Aluminum, steel, nylon
- Weight: 400g
- Working load limit: up to 150 kg for one person, and up to 200 kg when used for rescue (more information in the Instructions for Use and technical tips at www.petzl.com)
- Certification(s): EN 341 type 2 class A, CE EN 12841 type C, CE EN 15151-1, ANSI Z459.1, ANSI Z359.9, NFPA 2500 Technical Use, EAC, GB/T 38230 II A, XF 494:FZL-X-Q10/11.5
 - EN 341 type 2 class A when used with a PARALLEL 10.5 mm or AXIS 11 mm rope
 - EN 12841 type C when used with a 10 to 11.5 mm EN 1891 A rope
 - EN 15151-1 when used with a 9 to 11 mm rope
 - NFPA 2500 Technical Use when used with a 10 to 11.5 mm rope

Specifications by reference

Reference(s)	D021AA00	D021AA01
		
Color(s)	Yellow	Black
Rope compatibility	10 to 11.5 mm	10 to 11.5 mm
Made in	FR	FR
Guarantee	3 years	3 years
Inner Pack Count	1	1
Quantity Per Box	8	8
EAN	3342540821989	3342540821996

Related product(s)

- AXIS 11 mm
- PARALLEL 10.5 mm
- ASCENSION
- FOOTAPE
- CORDEX PLUS