

CSR2 PULLEYS



Classified to both NFPA and EN standards. Our CSR² (Confined Space Rescue) Pulley is strong and light, and accommodates life safety rope from 7/16 in (11 mm) to 1/2 in (13 mm). Ideal for industrial applications as well as many rescue operations, the CSR² uses our proprietary, patented locking system, which eliminates a toothed cam or Prusik so it can be easily and safely released while under load. The absence of the toothed cam means that even if the system is fully collapsed and pulled tight, it can still be released easily. Systems using a toothed cam must be raised even further before the cam can be released, which can be impossible if the system is fully collapsed without thinking about this problem ahead of time – causing potential problems with the load on the system becoming stuck. An integral thrust-bearing swivel reduces torque by aligning the pulley with the load, thereby increasing efficiency and safety. Its larger size allows for the easy application of rescue-size carabiners.

Machined from a solid block of aircraft-grade aluminum, the CSR² features a high-strength aluminum side plate, sealed bearings and anodized aluminum sheaves. The side bucket location allows for maximum lift height and full retraction of the system, and a removable bucket cover facilitates changing out lifeline with sewn terminations.

Features

- All-new stronger, lighter-weight design
- Compatible with 11-13 mm life safety rope
- CSR² Pulley MBS 40 kN (8,992 lbf)
- CSR² Double Pulley MBS 40 kN (8,992 lbf)
- Machined from solid block of aircraft-grade aluminum
- Pat. 7,419,138
- Made in USA

Classifications

- NFPA – General Use
- CE – EN 12278

Option	CSR2 Pulley
Item	300343
PRODUCT NAME	PULLEY, CSR2, CMC
PRODUCT WEIGHT	1.1 KG (2.5 LB)
SHEAVE TREAD SIZE	57 X 13 MM (2 1/4 X 1/2 IN)
COLOR	RED / GRAY
CLASSIFICATIONS	NFPA GENERAL USE, EN 12278
MBS	40 KN (8,992 LBF)

Option	CSR2 Double Pulley
Item	300342
PRODUCT NAME	PULLEY, CSR2 DOUBLE, CMC
PRODUCT WEIGHT	680 G (1.5 LB)
SHEAVE TREAD SIZE	57 X 13 MM (2 1/4 X 1/2 IN)
COLOR	GRAY
CLASSIFICATIONS	NFPA GENERAL USE, EN 12278
MBS	40 KN (8,992 LBF)