

Universe	Professional
Туре	Verticality
Category	Ropes
Subcategory	Low stretch kernmantel ropes



AXIS 11 mm


The AXIS 11 mm low stretch kernmantel rope is designed for work at height. The standard diameter ensures a good grip for easier handling. The EverFlex technology guarantees great flexibility and consistent performance over time. Rope available in six colors and four lengths.



The standard rope diameter ensures a good grip for easier handling.



EverFlex technology ensures great flexibility over time and under any conditions (water, dust, mud...), allowing it to maintain consistent handling and optimal performance with devices.



It is possible to order a rope of a specified length.



The addition of sewn terminations manufactured on one or both ends provides a ready-to-use rope. These terminations have a protective sheath that keeps the connector in position and facilitates handling.

Short Description

Low stretch kernmantel rope with good handling for work at height

Selling Points

- Standard diameter ensures a good grip for easier handling
- Consistent performance over time:
- construction with nylon core and polyester sheath, with specific weave
- EverFlex technology ensures great flexibility over time and under any conditions (water, dust, mud...), allowing it to maintain excellent handling and optimal performance with devices
- Available in six colors: white, yellow, black, blue, red and orange
- Standard lengths: 50, 100, 200 and 500 m
- Customization on request:
- option of ordering a rope of a specified length (up to 700 m)
- addition of sewn terminations manufactured on one or both ends, providing a ready-to-use rope. These terminations have a protective sheath that keeps the connector in position and facilitates handling. They are also stronger than a figure-eight knot

Specification

- Diameter: 11mm
- Material(s): polyester, nylon
- Certification(s): CE EN 1891 type A, UKCA, EAC, NFPA 2500 Technical Use, XF 494, ANSI Z459.1
- Weight per meter: 82g
- Strength tied with figure-eight knot: 19kN
 Strength with sewn termination: 22kN
 Impact force (factor 0,3): 5,2kN
 Number of factor 1 falls: 12
- Construction: 32 carrierPercentage of sheath: 41%Static elongation: 3%

Specifications by reference

Reference(s)	R074AA03	R074AA04	R074AA05	R074AA38
` ,	f	· ·		
	pt pt			
	pd ⁴ pd ⁴			
	*			
Length	50 m	50 m	50 m	50 m
Color(s)	white	yellow	black	blue
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	2	2	2	2
EAN	3342540816091	3342540816107	3342540816114	3342540822856
Reference(s)	R074AA39	R074AA40	R074AA09	R074AA10
				1
			je j	j.
			/	1
			/	
Length	50 m	50 m	100 m	100 m
Color(s)	red	orange	white	yellow
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	2	2	1	1
EAN	3342540822863	3342540822870	3342540816152	3342540816169
Reference(s)	R074AA11	R074AA12	R074AA13	R074AA14
1.0.0.0.00(0)		1	1.01.11.110	
Length	100 m	100 m	100 m	100 m
Color(s)	black	blue	red	orange
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	1	1	1	1
EAN	3342540816176	3342540816183	3342540816190	3342540816206
		•		
Reference(s)	R074AA21	R074AA22	R074AA23	R074AA24
	ar ar	/		
	** **			
	1			
1 41	000	1	000	000
Length	200 m	200 m	200 m	200 m
Color(s)	white CZ	yellow CZ	black CZ	blue CZ
Made in Guarantee				
Inner Pack Count	3 years	3 years	3 years	3 years
Quantity Per Box	1	' 1	1	1
EAN	3342540816275	3342540816282	3342540816299	3342540816305
		•		
Reference(s)	R074AA25	R074AA26	R074AA28	
			/	
			1	
Length	200 m	200 m	500 m	
	· · · · · · · · · · · · · · · · · · ·		· · · · · · · · · · · · · · · · · · ·	1

Color(s)	red	orange	white
Made in	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years
Inner Pack Count	1	1	1
Quantity Per Box	1	1	1
EAN	3342540816312	3342540816329	3342540816343

Accessory(ies) PROTEC

PROTEC SET CATERPILLAR ROLL MODULE

Related product(s) ASAP® LOCK I'D® S

I'D® S I'D® S ASAP® I'D® EVAC