



ULTIMA

ACCESS ROPE

CE EN1891-A

DIAMETER

Ø 10.5 mm

COLOUR OPTIONS

- WHITE BLUE
- RED

Also available in black

LENGTH OPTIONS

20, 40, 60, 100, 200, 900 meters
Other lengths available on request

TERMINATION

Available with 1 or 2 stitched eyes

The Ultima contains X-Braid technology which maintains its longterm flexibility. Patented Meetic technology fuses the core and sheath together without glue and therefore the user can still descend safely even if the rope is partially cut. A recent update has improved the stretch of the rope and added a highly visible sheath.

TECHNICAL SPECIFICATIONS



- Materials / construction: 32-strand Polyamide sheath with X-Braid Polyamide core
- Static resistance: 30kN
- Resistance with stitched eye: 22kN
- Resistance with figure of 8 knot: 19.5kN
- Mass per meter: 68gram
- Sheath percentage: 47%
- Sheath slippage: 0%
- Elongation 50/150Kg: 3%
- Knotability: 0.6
- Retraction with water: 2.2%
- Maximum lifespan: 10 years under normal working conditions

Reference: **MMG00U+++++**

KEY FEATURES

- Medium Low stretch
- Wear resistant sheath
- Fixed core construction for extra safety
- Highly visible colour combinations
- Retains it's flexibility over time

